



## C.I.Agent® Geomembrane Liner System with VIPOR Pump System

The C.I.Agent® Geomembrane Liner with the VIPOR Pump System allows cracked or porous containment systems as well as underground vaults to be retrofitted for SPCC-compliant secondary oil containment. The C.I.Agent® VIPOR uses proven C.I.Agent Solutions oil solidification technology to prevent any hydrocarbons from being automatically discharged. The safe, unattended discharges from the VIPOR will save crew time from frequent manual dewatering, while the Geomembrane Liner will ensure no hydrocarbon contamination leaches into the environment. All C.I.Agent® Geomembrane Liner Solutions are custom manufactured and designed to the customer's exact engineered specifications.

### Ideal Solution for Retrofitting These Types of Existing Containment

- Concrete Walls, cracked
- Concrete Walls, holds water
- Concrete Walls, porous floor
- Composite Walls, holds water
- Composite Walls, porous floor
- Concrete Vault, containment cracked
- Concrete Vault, containment holds water
- Sumps or Collection Systems

### Features and Benefits

- Supports high flow rates at low head
- Aesthetically pleasing
- Fire suppression/Fire resistant capabilities
- Passive containment
- Can solidify all types of hydrocarbons (including FR3)

Contact us today to explore how we can solve your oil containment challenges

**C.I.Agent Solutions®**

www.ciagent.com | 866-242-4368 | 502-267-0101